

## Basic Ø100 2 Fixing point

LEVELING FEET > BASIC

The BASIC series, with plastic baseplate and fully threaded spindle is the standard choice for the industrial environments. The spindle can be made with flat or hexagonal key wrench and is available in two different materials, zinc plated steel or stainless steel. Maximum compressive strength (static load) as in the table, maximum tensile strength (static load) 500 N.



SS BASIC FOOT - D 100 M16X158

Article-Nr: P95602

### Technical features

|                               |                 |
|-------------------------------|-----------------|
| <b>Unit of measure</b>        | Ea              |
| <b>Design</b>                 | Standard        |
| <b>Base material</b>          | Plastic         |
| <b>Diameter</b>               | 100 mm          |
| <b>Fixing point</b>           | 2               |
| <b>Anti-slip</b>              | No              |
| <b>Temperature range dry:</b> | -20÷120 °C      |
| <b>Temperature range wet:</b> | -20÷120 °C      |
| <b>L:</b>                     | 135 mm          |
| <b>Key slot:</b>              | Standard        |
| <b>Spindle material:</b>      | Stainless steel |
| <b>Thread size:</b>           | M16             |
| <b>H tot:</b>                 | 158             |
| <b>Design:</b>                | Standard        |

---

|                |                  |
|----------------|------------------|
| <b>Key 1:</b>  | 13 mm            |
| <b>Ball D:</b> | 10 mm            |
|                | Max Load 15000 N |

---

